

Life Science

It's in your hands.



Excellence in Biorepository



BIOBANKING

- Conceptual Design
- Engineering
- IQ / OQ
- ...

▶ p. 8

Multilayer Vacuum Isolated Pipes

▶ See Brochure



APOLLO® Nitrogen Storage Vessel

50 - 350 l capacity

▶ p. 44

ALPHA / JUNO® Nitrogen Storage & Transport Vessel

6 - 30 l capacity

▶ p. 40



BIOSAFE® MARATHON

Dry shipping vessel up to 500 vials, 2 ml.

▶ p. 38

BIOSAFE® VENUS

For small to medium sample volumes up to 6,000 vials, 2 ml.

▶ p. 34



BIOSAFE® Working / Wide Neck Series

120 - 220 - 420 - 820
up to 54,400 vials, 2 ml

▶ p. 10



BIOSAFE® Longtime / Narrow Neck Series

500 - 800 - 1800 - 2400
up to 122,400 vials, 2 ml

▶ p. 14

BIOSAFE® smart

The digital brain of your biobank

▶ p. 9



BIOSAFE® iTrack

Intelligent sample management software

▶ p. 28

BIOSAFE® Rack-System

Standardised and individual design

▶ p. 26



Cryopreservation using liquid nitrogen is a well-established and trusted technique across science, research, medicine, and environmental studies. The process involves safely storing materials at -190°C in the gas phase, within an inert atmosphere, ensuring optimal preservation of valuable medical and biological samples.

Cryotherm, a leading supplier of storage, transfer, and transport systems, has been a renowned manufacturer of cryogenic technology products and services for almost 60 years.

BIOSAFE® liquid nitrogen freezers by Cryotherm are synonymous with quality and safety. Specializing in cryogenic storage solutions, BIOSAFE® ensures the safe handling and preservation of biological and medical materials at extremely low temperatures. Our expertise, advanced technology, and deep-know-how make choosing BIOSAFE® a straightforward decision. With ongoing innovation, we have expanded the BIOSAFE® line to include new cutting-edge life science products.

Our BIOSAFE®-systems consist of:

- ▶ BIOSAFE® / VENUS cryogenic storage vessels, crafted from stainless steel or aluminum, and are designed for the storage of both large and small quantities.
- ▶ BIOSAFE® smart unit for controlling the liquid nitrogen level and monitoring the environment inside your BIOSAFE® system.
- ▶ BIOSAFE® VENUS – our aluminum series designed for small to medium sample volumes.
- ▶ BIOSAFE® MARATHON – a dry shipping container for the safe transport of your biological samples.
- ▶ BIOSAFE® GO - the practical and ergonomic workbench for the safe loading of your biological samples into vials, boxes, racks, and more.

BIOSAFE® - Systems An overview of our life science family.	2 - 3
Safety Equipment Your safety is our priority.	6 - 7
Biobanking - BIOSAFE® smart The 'digital brain' of your biobank.	8 - 9
BIOSAFE® 120 - 220 - 420 - 820 The secure BIOSAFE® wide neck storage vessel series - for up to 54,400 cryogenic vials 2 ml	10 - 13
BIOSAFE® 500 - 800 - 1800 - 2400 The narrow neck BIOSAFE® Stainless Steel Series - for up to 122,400 cryogenic vials 2 ml	14 - 17
BIOSAFE® Layout Plans Overview of possible ways of arranging different inventory systems	18 - 25
BIOSAFE® Inventory Systems Overview	26 - 27
BIOSAFE® iTrack Your intelligent sample management.	28 - 31
BIOSAFE® GO Ideal for handling your samples.	32
BIOSAFE® VENUS The safe storage for your samples - for up to 6,000 cryogenic vials 2 ml	34 - 37
BIOSAFE® MARATHON 25 MD For safe shipment of your samples - for up to 500 cryogenic vials 2 ml	38 - 39
ALPHA and JUNO® Unpressurized vessel series for transport with a capacity of 6 to 30 l	40 - 41
STELLA® Liquid nitrogen „to go“ - with a capacity of 0,6 to 63 l	42 - 43
APOLLO® Vacuum super-insulated storage and transport vessel for liquid nitrogen with a capacity of 50 to 350 l	44 - 47



Body Protection



Cryo-Aprons	Description	Item No.
	Length: approx. 920 mm, designed for protection from cryogenic vapors and splashes within a temperature range down to -160°C	77031519
	Length: approx. 1,380 mm, designed for protection from cryogenic vapors and splashes within a temperature range down to -160°C	77031520
Cryo-Protective Shield and Goggles		
Cryo-protective sign and inspection glass 4	head protection signs of vulcanized fibre foam padded dimensions: (WxH) 460 x 190 mm	77031452
Safety goggles with side protection 3		0794189
Sign		
"Wear eye protection" 6	Adhesive Foil Ø 20 cm Symbol	78210204



Cryo-Protective Equipment Full Set



Description	Item No.
Incl. Cryo-Gloves 1, Cryo-Apron 4, Cryo-Protective sign 5 and 2 Warning Signs 6 + 7	78400851

Cryo-Gloves, waterproof



Description Hand protection, 5 fingers, down to -160° C	Length	Size	Item No.
Length: ca. 300 mm 1	Wrist	S	78400613
Length: ca. 300 mm	Wrist	M	78213086
Length: ca. 300 mm	Wrist	L	77031450
Length: ca. 300 mm	Wrist	XL	78400823
Length: ca. 400 mm 2	Forearm	S	78400843
Length: ca. 400 mm	Forearm	M	78400180
Length: ca. 400 mm	Forearm	L	78400887
Length: ca. 400 mm	Forearm	XL	78400856
Length: ca. 500 mm	Elbow	M	78400899
Length: ca. 500 mm	Elbow	L	77031451
Length: ca. 500 mm	Elbow	XL	78211327



The One-Stop Biobank



60

YEARS Ice Cold Experience

Since 60 years we have been working closely with scientists and researchers.



On-site Consultation

Our experts are looking forward to consult with you!



Excellence in Engineering

Your Turnkey Biobank: Everything in one full package!



Service / 24/7 Hotline and Maintenance

Always close to our customers.



Monitoring

Clever management of your entire biobank. Even from afar.



BIOSAFE® smart

The digital brain of your biobank.

Biobanking

4.0

100 % in Control

Thanks to optional electromechanical locking, your samples are securely protected against unauthorized access. Dual access control via RFID transponder and PIN code ensures enhanced security. All activities are logged in compliance with GMP and FDA CFR 21 Part 11 regulations.

Big Data

From monitoring to recording to evaluation of the sample cycle - Let data speak.

Touch Screen

Intuitive 8.8" multifunctional panel with a bright, full-color touch display for optimal functionality.

Conversion Kit*

Your existing BIOSAFE® repository freezer can be updated with new BIOSAFE® smart. Item No. 78221956

* Cryotherm verifies feasibility.

High Durability

Protected by a sturdy glass panel, ideal for aseptic and medical environments.



Extensive Special Equipment

Various options for linking components such as warmgas bypass, UPS battery, lid lock, additional temperature sensors and much more.

Select your Software-Package

Config-Version

On-site BIOSAFE® monitoring via color display (included).

BIOSAFE® Info.View

On-site and remote monitoring of BIOSAFE® including secure data analysis and transfer, with the ability to connect up to 254 BIOSAFE® units in up to 10 cryobanks. optional: Item No. 78216677

BIOSAFE® Info.Alarm

contains all advantages of BIOSAFE® Info.View incl. messenger function via eMail. **System requirements:** Customer internet connection and email account. optional: Item No. 78216678

BIOSAFE® 120 - 220 - 420 - 820

Our secure BIOSAFE® Wide Neck Storage Vessel Series.

All Advantages at a Glance



Storing samples for

Our BIOSAFE® systems 120 to 820 are optimised for maximum capacity with minimised external dimensions. The large, thermodynamically optimised, vacuum-insulated lid that comes with an attractive design makes it possible to access stored materials in just seconds.

Filling of samples takes place through the wide neck opening in the freely accessible storage compartment. The solid construction, made of polished, stainless steel, ensures maximum life time and a low evaporation rate. A combined vacuum closure and safety device for the vacuum chamber provides additional security.



BIOSAFE® 120 - 220 - 420 - 820

The Practical Working Biorepository System.



All Advantages at a Glance



Double the Safety!
Mechanically and
(optional) electronically
lockable lid.

Distinctive & Sophisticated:
Ergonomic lifting and swivelling
mechanism / Low, user-friendly
vessel height.

Ahead of the Market:
Our integrated BIOSAFE®
smart control
for level control and vessel
monitoring.

TOP Accessibility
to your samples, ideal for
frequent usage.

Optimised Storage Capacity
by utilising space-saving smart
rack systems.

Well-thought-out:
Depending on the vessel size,
high nitrogen reserves below
the shelf floor will last several
days.

High Storage Capacity
for up to 54.400 samples,
2 ml vials.

Low Evaporation Rates

Smooth surfaces,
that are **easy to disinfect**
- even on top of the lid.



BIOSAFE® 120 - 220 - 420 - 820

Visual Insights.




BIOSAFE® 120 - 220 - 420 - 820

Ideal for Routine Work with Biological-medical Samples.

Technical Data

		<div>NEW</div>			
Wide-neck BIOSAFE®		120	220	420	820
Neck opening/Inner Diameter					
<div>A</div>	[mm]	514	664	854	1,091
LN2 Capacity (Vapor Storage)	[l]	21	35	57	140
Weight, empty	[kg]	100	175	225	600
Outer Diameter	<div>B</div> [mm]	560	710	900	1,150
Overall height	<div>C</div> [mm]	1,420*	1,680	1,680	2,222
Liftover height**	<div>D</div> [mm]	1,050	1,070	1,070	970
Usable Internal Height	[mm]	625	625	625	915***
Caster diameter	[mm]	-	80	80	63
Evaporation rate	[%/day]	2.3	2.0	1.5	1,2
Gross Capacity	[l]	151	251	415	888

*) without rollerbase
 **) BIOSAFE® 820 measured from step, BIOSAFE® 120 / 220 / 420 from bottom
 ***) Max. operating height, without swivelling tray.



Storage Capacities

Wide-neck BIOSAFE®	120	220	420	820
2 ml vials [max./up to]	7.000	13.000	23.000	54.400
50ml cassettes** CryoMACS 50 bags	288	512	896	2.100
500ml cassettes** CryoMACS 500 bags	144	240	480	1.056
SBS boxes (up to 30mm height) [max./up to]	247	399	779	1.456
in goblets (2 per canister)	2.432	4.032	7.040	10.368
Flat cassettes IVF Formidable	1.536	3.840	7.296	-
in goblets (4 to 5 per canister)	132.240	219.240	382.800	704.700
0,25 ml straws IVF Formidable	18.432	46.080	87.552	-
in goblets (2 per canister)	912	1.512	2.640	3.888
Vial holder IVF Formidable	512	1.280	2.432	-

**) 25ml and 250ml cassettes available upon request



The Narrow Neck BIOSAFE® Series.



© Photo:



All Advantages at a Glance



Storing samples for



Picture of the BIOSAFE® 800

Cryogenic facilities with > 100 freezers
© Photo Fraunhofer IBMT, Dr. Obergrießer

Our BIOSAFE® systems, ranging from 500 to 2400 are designed for maximum capacity with minimal consumption. The smooth-running aluminum carousel ensures optimal temperature uniformity inside the BIOSAFE® freezer, safeguarding your valuable samples.

BIOSAFE® 500 - 800 - 1800 - 2400

The Safe Bank. The Long-term Storage BIOSAFE® Series.

All Advantages at a Glance



Zero-gravity Lid Technology

A convenient spring supported lid lets you open BIOSAFE® with one hand and zero effort.

Double the Safety!

Mechanically and (optional) electronically lockable lid.

Ahead of the Market: Integrated BIOSAFE® smart-control

provides level control and vessel monitoring

TOP-Handling

Smooth carousel for quick and safe usage.

Best in its Class!

Store up to 122,400 2 ml samples in just one BIOSAFE® vessel. Unbeatable amount!

Sophisticated Ergonomics

Convenient steps, handles and a user-friendly low operating height ensure safe and comfortable handling.

More than just safe

Numerous options for redundant vessel monitoring for GMP-compliant applications.




BIOSAFE® 500 - 800 - 1800 - 2400

Our Narrow Neck BIOSAFE® Stainless Steel Series.

Technical Data



Longtime storage BIOSAFE®		500	800	1800	2400
Neck diameter	A [mm]	450	520	830	830
LIN Capacity under platform	[l]	50	116	287	320
Weight, empty	[kg]	320	560	1,100	1,300
Diameter, outside	B [mm]	890	1,058	1,500	1,650
Diameter, inside / carousel	[mm]	795	966	1,346	1,500
Total height	C [mm]	1,340	1,830	2,150	2,150
Operating height	D [mm]	1,014	1,080	1,070	1,070
Installation altitude for racks	[mm]	800	800	915	915
Caster diameter	[mm]	80	80	100	100
Evaporation rate	[%/day]	1,2	1,0	0,7	0,6
Gross capacity	[l]	490	760	1.880	2.300



Storage Capacities



Longtime storage BIOSAFE®		500	800	1800	2400
2 ml vials	[max./up to]	26.950	40.600	94.000	122.400
50ml cassettes**	CryoMACS 50 bags	1.080	1.485	3.800	4.600
500ml cassettes**	CryoMACS 500 bags	480	780	1.824	2.400
SBS boxes (up to 30mm height)	[max./up to]	768	1.176	2.600	3.328
Flat cassettes	in goblets (2 or 3 per canister)	6.400	9.408	26.496	31.488
025 ml straws	in goblets (5 per canister)	435.000	617.700	1.200.600	1.426.800
Vial holder	in goblets (2 or 3 per canister)	2.400	3.528	9.936	11.808

***) 25ml and 250ml cassettes available upon request

Automation in the Cryobank




Picture of a BIOSAFE® 8800, with a capacity of 1 mil. vials 2 ml for individual cryobanking project.

BIOSAFE® 120 - 220 - 420 - 820

Layout for Racks with Cryoboxes - 2 ml vials

BIOSAFE® 120


Storage Capacity: Up to 7.000 Vials



- **7 Racks à 570 x 140 x 136 mm, 10 Levels**
Item No.: 78221976 for Rack per piece

BIOSAFE® 220


Storage Capacity: Up to 13.000 Vials



- **12 Racks à 570 x 140 x 136 mm, 10 Levels**
Item No.: 78221976 for Rack per piece
- **4 Racks à 570 x 84 x 78 mm, 10 Levels**
Item No.: 78222196 for Rack per piece

BIOSAFE® 420

Storage Capacity: Up to 23.000 Vials



- **20 Racks à 570 x 140 x 136 mm, 10 Levels**
Item No.: 78221976 for Rack per piece
- **12 Racks à 570 x 84 x 78 mm, 10 Levels**
Item No.: 78222196 for Rack per piece

BIOSAFE® 820

Storage Capacity: Up to 54.400 Vials



Without Handling Tray:

- **32 Racks à 915 x 140 x 136 mm, 16 Levels**
Item No.: 78221742 for Rack per piece
- **8 Racks à 915 x 84 x 78 mm, 16 Levels**
Item No.: 78222199 for Rack per piece

With Handling Tray:


- **32 Racks à 800 x 140 x 136 mm, 14 Levels**
Item No.: 78221978 for Rack per piece
- **8 Racks à 800 x 84 x 78 mm, 14 Levels**
Item No.: 78222198 for Rack per piece

BIOSAFE® 500 - 800 - 1800 - 2400

Layout for Racks with Cryoboxes - 2 ml vials

BIOSAFE® 500


Storage Capacity: Up to 26.950 Vials



- **18 Racks à 800 x 140 x 136 mm, 14 Levels**
Item No.: 78221978 for Rack per piece
- **5 Racks à 800 x 84 x 78 mm, 14 Levels**
Item No.: 78222198 for Smart-Rack per piece

BIOSAFE® 800


Storage Capacity: Up to 40.600 Vials



- **26 Racks à 800 x 140 x 136 mm, 14 Levels**
Item No.: 78221978 for Rack per piece
- **12 Racks à 800 x 84 x 78 mm, 14 Levels**
Item No.: 78222198 for Rack per piece

BIOSAFE® 1800


Storage Capacity: Up to 94.000 Vials



- **52 Racks à 915 x 140 x 136 mm, 16 Levels**
Item No.: 78221742 for Rack per piece
- **27 Racks à 915 x 84 x 78 mm, 16 Levels**
Item No.: 78222199 for Rack per piece

BIOSAFE® 2400

Storage Capacity: Up to 122.400 Vials




- **71 Racks à 915 x 140 x 136 mm, 16 Levels**
Item No.: 78221742 for Rack per piece
- **22 Racks à 915 x 84 x 78 mm, 16 Levels**
Item No.: 78222199 for Rack per piece

BIOSAFE® 120 - 220 - 420 - 820


Layout for Racks with SBS-Boxes (max. 30mm Height)

BIOSAFE® 120
 Storage Capacity: Up to 247 SBS Boxes




- 13 Smart-Racks à 620 x 91 x 130 mm, 19 Levels
- Item No.: 78226071 for Rack per piece

BIOSAFE® 220
 Storage Capacity: Up to 399 SBS Boxes




- 21 Racks à 620 x 91 x 130 mm, 19 Levels
- Item No.: 78226071 for Rack per piece

BIOSAFE® 420
 Storage Capacity: Up to 779 SBS Boxes



- 41 Racks à 620 x 91 x 130 mm, 19 Levels
- Item No.: 78226071 for Smart-Rack per piece

BIOSAFE® 820
 Storage Capacity: Up to 1.456 SBS Boxes




- Without Handling Tray
- 56 Racks à 915 x 91 x 130 mm, 26 Levels
- Item No.: 78226074 for Rack per piece
- With Handling Tray
- 56 Racks à 800 x 91 x 130 mm, 24 Levels
- Item No.: 78226073 for Rack per piece

BIOSAFE® 500 - 800 - 1800 - 2400


Layout for Racks with SBS-Boxes (max. 30mm Height)

BIOSAFE® 500
 Storage Capacity: Up to 768 SBS Boxes




- 32 Racks à 800 x 91 x 130 mm, 24 Levels
- Item No.: 78226073 for Rack per piece

BIOSAFE® 800
 Storage Capacity: Up to 1.176 SBS Boxes




- 49 Racks à 800 x 91 x 130 mm, 24 Levels
- Item No.: 78226073 for Rack per piece

BIOSAFE® 1800
 Storage Capacity: Up to 2.600 SBS Boxes



- 100 Racks à 915 x 91 x 130 mm, 26 Levels
- Item No.: 78226074 for Rack per piece

BIOSAFE® 2400
 Storage Capacity: Up to 3.328 SBS Boxes




- 128 Racks à 915 x 91 x 130 mm, 26 Levels
- Item No.: 78226074 for Rack per piece

BIOSAFE® 120 - 220 - 420 - 820

Layout for Cassettes with 50 ml Bags (CryoMACS50)

BIOSAFE® 120


Storage Capacity: Up to 288 Bags 50 ml each



- 9 Racks à 575 x 95 x 165 mm, 32 Levels
Item No.: 77031511 for Rack per piece

BIOSAFE® 220


Storage Capacity: Up to 512 Bags 50 ml each



- 16 Racks à 575 x 95 x 165 mm, 32 Levels
Item No.: 77031511 for Rack per piece

BIOSAFE® 420


Storage Capacity: Up to 896 Bags 50 ml each



- 28 Racks à 575 x 95 x 165 mm, 32 Levels
Item No.: 77031511 for Rack per piece

BIOSAFE® 820

Storage Capacity: Up to 2.100 Bags 50 ml each




- Without Handling Tray
42 Racks à 900 x 95 x 165 mm, 50 Levels
Item No.: 78226077 for Rack per piece
- With Handling Tray
42 Racks à 800 x 95 x 165 mm, 45 Levels
Item No.: 78215709 for Rack per piece

BIOSAFE® 500 - 800 - 1800 - 2400

Layout for Cassettes with 50 ml Bags (CryoMACS50)

BIOSAFE® 500

Storage Capacity: Up to 1.080 Bags 50 ml each



- 24 Racks à 800 x 95 x 165 mm, 45 Levels
Item No.: 78215709 for Rack per piece

BIOSAFE® 800

Storage Capacity: Up to 1.485 Bags 50ml



- 33 Racks à 800 x 95 x 165 mm, 45 Levels
Item No.: 78215709 for Rack per piece

BIOSAFE® 1800


Storage Capacity: Up to 3.800 Bags 50ml



- 76 Racks à 900 x 95 x 165 mm, 50 Levels
Item No.: 78226077 for Rack per piece

BIOSAFE® 2400

Storage Capacity: Up to 4.600 Bags 50ml



- 92 Racks à 900 x 95 x 165 mm, 50 Levels
Item No.: 78226077 for Rack per piece

BIOSAFE® 120 - 220 - 420 - 820


Layout for Cassettes with 500ml bags (CryoMACS500)

BIOSAFE® 120
Storage Capacity: Up to 144 Bags 500 ml each




- 6 Racks à 620 x 80 x 280 mm, 4 Levels
Item No.: 78202831 for Rack per piece

BIOSAFE® 220
Storage Capacity: Up to 240 Bags 500 ml




- 10 Racks à 620 x 80 x 280 mm, 4 Levels
Item No.: 78202831 for Rack per piece

BIOSAFE® 420
Storage Capacity: Up to 480 Bags 500 ml each



- 20 Racks à 620 x 80 x 280 mm, 4 Levels
Item No.: 78202831 for Rack per piece

BIOSAFE® 820
Storage Capacity: Up to 1.056 Bags 500 ml each




- Without Handling Tray
- 44 Racks à 915 x 52 x 280 mm, 6 Levels
Item No.: 78226076 for Rack per piece
- With Handling Tray
- 44 Racks à 780 x 52 x 280 mm, 5 Levels
Item No.: 78214757 for Rack per piece

BIOSAFE® 500 - 800 - 1800 - 2400

Layout for Cassettes with 500 ml bags (CRYOMACS500)




BIOSAFE® 500
Storage Capacity: Up to 480 Bags 500 ml each




- 24 Racks à 780 x 52 x 280 mm, 5 Levels
Item No.: 78214757 for Rack per piece

BIOSAFE® 800
Storage Capacity: Up to 780 Bags 500 ml each



- 39 Racks à 780 x 52 x 280 mm, 5 Levels
Item No.: 78214757 for Rack per piece

BIOSAFE® 1800
Storage Capacity: Up to 1.824 Bags 500 ml each



- 76 Racks à 915 x 52 x 280 mm, 6 Levels
Item No.: 78226076 for Rack per piece

BIOSAFE® 2400
Storage Capacity: Up to 2.400 Bags 500 ml each



- 100 Racks à 915 x 52 x 280 mm, 6 Levels
Item No.: 78226076 for Rack per piece

Your Needed Packaging



Our Various Solutions



For your BIOSAFE® Repository Freezers




GAS PHASE: liquid under the platform; samples immersed in N₂ vapours (temperatures around -180°C)

LIQUID PHASE: Samples completely immersed in liquid nitrogen (temperatures around -190°C)

Possibility of both types of cryopreservation through probe length adaptation



All Advantages at a Glance




New Smart racks

- ▶ High storage capacity with new High Efficiency system
- ▶ Safety fixation system
- ▶ Maximum protection for your samples
- ▶ Various heights for flexible use and compatibility with all biorepository freezers
- ▶ Variable arrangements for setting your own order system
- ▶ Low tare weight due to sturdy aluminium construction
- ▶ Transparency by means of sample management system



For more information
BIOSAFE® iTrack page 25

Rack of **stainless steel** with **uneven** heat distribution:




Cryotherm rack of **aluminium** with **even** heat distribution:



Cryo vessels

temperature in °C



For detailed information please regard dedicated brochure for inventory systems.



Functional Favorite



BIOSAFE® smart is an on-site vessel monitoring system with the following abilities:

- Level control and monitoring, automatic filling and temperature logging
- Monitoring and evaluation of alarms and events
- Data analysis and transfer according to GMP / FDA CRF 21 Part 11
- Access restriction to control functions on administration level via PIN or RFID transponder
- Visual and audible alarm on the touch-display, with existing internet connection with BIOSAFE® View Info Software also as e-mail
- Forwarding of alarms (potential-free contacts) and temperature (4-20mA signal)
- Possibility to connect a redundant level measurement for alarming purposes (optional for BIOSAFE® narrow neck lines)
- Mechanical and electrical lid locking (optional for BIOSAFE® narrow neck lines)
- Temperature monitoring with up to three temperature sensors
- Other optional equipment: Warmgas bypass, UPS backup battery

Other clear BIOSAFE® smart plus points are:

- Audit trail on control actions and settings
- Networking via TCP/IP or Modbus (option) of up to 256 devices via their own physical, static subnet and a remote desktop connection.
- Extension to comprehensive cryobank management via BIOSAFE® smart BSIO Box (option)
- Linking options with existing systems via several digital and potential-free inputs and outputs, as well as analog connections
- PLC function with five freely programmable channels for extensive adaptation to individual Adaptation to individual customer requirements thanks to BIOSAFE® View Software

Main Options

BIOSAFE® 120 - 2400

☒ Item No.	Short text	Pcs
☐ 78202845	Rollerbase for BIOSAFE® 120	—
☐ 78202830	Transport aid for BIOSAFE® 220 - 800	—
☐ 78224556	Temp. booster gas phase storage BIOSAFE® 120	—
☐ 78224557	Temp. booster gas phase storage BIOSAFE® 220	—
☐ 78224115	Temp. booster gas phase storage BIOSAFE® 420	—
☐ 78216677	BIOSAFE®-view Info	—
☐ 78216678	BIOSAFE®-view InfoAlarm	—
☐ 78217372	MODBUS for BIOSAFE® smart	—
☐ 78216670	Network switch 8x	—
☐ 78222466	Second solenoid valve	—
☐ 78222354	Warmgas bypass BIOSAFE® smart 120 - 800	—
☐ 78222355	Warmgas bypass with add. Main-valve, BIOSAFE® smart 120 - 800	—
☐ 78221877	Warmgas bypass BIOSAFE® smart 1800 - 2400	—



Factory setting of the BIOSAFE® series to gas phase storage, please add item number 78225101 for setting to liquid phase storage.

Your BIOSAFE® Biorepository Freezer

BIOSAFE® 120 - 2400

☒ Item No.	☒ Item No.	Short text	Pcs
☐ 78221903	☐ 78221879	BIOSAFE® 120 smart	—
☐ 78221906	☐ 78221882	BIOSAFE® 220 smart	—
☐ 78221909	☐ 78221885	BIOSAFE® 420 smart	—
☐ 78221912	☐ 78221888	BIOSAFE® 500 smart	—
☐ 78223148	☐ 78223145	BIOSAFE® 800 smart	—
☐ 78224877	☐ 78224880	BIOSAFE® 820 smart	—
☐ 78223473	☐ 78223480	BIOSAFE® 1800 smart	—
☐ 78221924	☐ 78221600	BIOSAFE® 2400 smart	—
☐ 78221956		Conversion kit for existing BIOSAFE® repository freezer	—
☐ 78217486		BIOSAFE®-smart I/O-Box incl. cabinet	—
☐ 78222361		Temperatur sensor for BIOSAFE® smart (additional)	—
☐ 78222353		Battery backup 24VDC for BIOSAFE® smart	—



Tracking your Cryogenic Samples



Example of
2D Scanner
Not included in delivery.

BIOSAFE® iTrack is a central database that can manage your stored samples based on their storage position. It can easily be adapted to the individual needs of your biobank. The necessary basic information and additional user defined information is linked to each sample. This information may be different data templates, logistics information or process data.

All Advantages at a Glance

- User friendly storage management
- FDA 21 CFR Part 11 compliance
- Sample based temperature logging
- Highest degree of data encryption for your sensitive data
- Developed, tested and documented according to ISO 13485, ISO 62304, IEC 62366
- User-defined storage structures/layouts
- Comprehensive storage level access rights
- Barcode scanner and RFID support
- User-defined sample data templates
- Visualisation of storage locations and containers
- Single/Multiple sample check in/out
- Single/Multiple sample data modification
- Comprehensive reporting PDF
- Comprehensive data Exports PDF/CSV
- Multiple IDs possible
- Windows based system
- Multi-site/multi database support
- 2D Flatbed scanner support
- Lab OS Web Access /Customer requests
- Electronic signatures ("A face four eyes check" feature)



Item Numbers

With BIOSAFE® iTrack we offer you various options for software support, whether for vials, bags, straws or individual packaging for your samples,

BIOSAFE® iTrack		
☒	Item no.	
☐	78217135	BIOSAFE® iTrack 3 years - Software support for a term of three years, for up to 5 users, one computer installation (on one laptop or PC)
☐	78217140	BIOSAFE® iTrack 3 years - Extra CAL license for one additional computer installation
☐	78217142	BIOSAFE® iTrack 3 years - Extension for each additional user
☐	78217137	BIOSAFE® iTrack 3 years - Webaccess* for the secure mobile access to sample database with search and read permission (search, request & order samples)
☐	78217136	BIOSAFE® iTrack 5 years - Software support for a term of three years, for up to 5 users, one computer installation (on one PC, laptop)
☐	78216916	BIOSAFE® iTrack 5 years - Extra CAL license for one additional computer installation
☐	78216917	BIOSAFE® iTrack 5 years - Extension for each additional user
☐	78217138	BIOSAFE® iTrack 5 years - Webaccess* for the secure mobile access to sample database with search and read permission (search, request & order samples)
☐	78217143	BIOSAFE® iTrack Remote-Training**

*) Access depending on administrative authorization . **) Remote maintenance by telephone or remote access are limited to a maximum, monthly hourly quota of three hours within the corresponding contract period.

All Advantages at a Glance

BIOSAFE® GO is the practical and ergonomic workbench for the safe further processing of your biological samples in vials, boxes, racks, etc. Optimal for the the transport of large sample volumes from one container to another other container in a cryobank, e.g. relocation.

- ▶ Sample handling and transport of two horizontal towers in cryogenic N2 gas phase
- ▶ Vacuum insulated storage container mounted on a stainless steel transport cart
- ▶ Additional opening with plug for level measurement
- ▶ Temperature booster made of aluminum for low temperatures in the working chamber
- ▶ LN2 filling device with ball valve and 2.5 m insulated filling hose connection
- ▶ Two accesses for T-probes and mounting options for temperature logger
- ▶ Movable sample handling table
- ▶ Two separately opening lid halves

Datalogger (included)
 for temperature recordings,
 with GPS on request. Item No. 78224306

exemplary
 illustration

Technical Data

BIOSAFE® GO		
Geometrical capacity	[l]	265
LN2 capacity	[l]	approx. 20
Total lenght x width x height	[mm]	1,465 x 625 x 975
Inner length x width x height	[mm]	1,030 x 446 x 450
Opening, access (length x width)	[mm]	1,030 x 446
Operating height	[mm]	930
Storage height	[mm]	385
Filling height	[mm]	80
Weight empty	[kg]	160
Weight full (N2)	[kg]	176
Evaporation rate	[l/h]	1,5
Castor diameter	[mm]	125
With 2 lids, ball valve 3/8", safety relief valve 5 bar, insulated decanting hose length 2.5m and transport stopper DN50		Item No. 78224791



© Photo: CREAPHARM BIOSERVICES




All Advantages at a Glance



- The safe aluminum storage vessel.
Ideal for biological-medical samples.
- ▶ For up to 6,000 samples 2 ml vials in gas or liquid phase
 - ▶ For straws in up to 96 goblets à 65 mm
 - ▶ For up to 108 bags 250 / 500 ml

Table for dimensions



Technical Data



BIOSAFE® VENUS		150	180
Neck diameter	[mm]	216	216
Weight, empty (as delivered, with rack system and BIOSAFE® smart electronics)	[kg]	96	105
Weight, full (in real operation with LIN, max.)	[kg]	192	245
Total height	A [mm]	1,100	1,215
Height of vessel	B [mm]	950	1,065
Height of roller base	C [mm]	140	140
Diameter, outside	E [mm]	678	678
Depth max.	F [mm]	840	840
Width max.	D [mm]	820	820
Daily evaporation	[%/day]*	0.79	0.54
Static holding time	[days]*	148	181
Static holding time	[days]*	13	13

*) The daily evaporation rate and the static holding time were determined at 20 degrees Celsius, 1013 hectopascal, with the vessel standing still, lid closed and without accessories. These are nominal values that may change depending on the use and age of the container.

Folding lid
Item No. 78217562

Insulation plug
Item No. 78217561



Smart-rack system for a comfortable and safe acces to your samples



Individual numbering for clear placement


Storage Capacities



BIOSAFE® VENUS		150	180
Liquid phase / Gas phase			
Nominal volume	[l]	120	175
Racks (aluminum)	[piece]	6	6
Number of levels usable	[quantity]	8	7/8
2 ml cryogenic vials in 10x10 boxes	[up to]	4,800	4,200
Size of cryogenic boxes 10x10 (hxwxd)	[mm]	132 x 132 x 53	132 x 132 x 53
Daisy goblets	[up to]	72	48
Bags 250/500 ml (77031488)	[up to]	54	54

Further vessel sizes and accessories upon request.

Dedicated Inventory Systems & Options for the VENUS



Smart Rack for Vials

VENUS 150 Item No. 78217554
VENUS 180 Item No. 78217555



Cryoboxes for 2 ml Vials:
for 9x9 Item No. 78214364
for 10x10 Item No. 78212859

Drawer for goblets

Rack for Goblets

VENUS 150 Item No. 78217556
VENUS 180 Item No. 78217557



Smart Rack for Bags

VENUS 150 Item No. 78217558
VENUS 180 Item No. 78217559




Cryo-Gloves

Length: ca. 400 mm
Item No.
Size S: 78400843
Size M: 78400180
Size L: 78400887
Size XL: 78400856



Cryo-protective Shield

Item No. 77031452



Roller base

Ø 687 mm (interior), height 140 mm
with five swivel castors, three of them lockable: Item No. 78217560



Multicolor goblets with lid and divider for an easy identification



Gas Phase Storage

Your samples are stored in the gas phase, without contact to liquid nitrogen. The usable levels secure the storage in gas phase.



Liquid Phase Storage

Your samples are stored up to 100% in the liquid phase at temperatures down to -196°C.

BIOSAFE® VENUS

equipped with BIOSAFE® smart.

Functional Favorite



- BIOSAFE® smart is an on-site vessel monitoring system with the following abilities:

 - Level control and monitoring, automatic filling and temperature logging
 - Monitoring and evaluation of alarms and events
 - Data analysis and transfer according to GMP / FDA CRF 21 Part 11
 - Access restriction to control functions on administration level via PIN or RFID transponder
 - Visual and audible alarm on the touch-display, with existing internet connection with BIOSAFE® View Info Software also as e-mail
- Forwarding of alarms (potential-free contacts) and temperature (4-20mA signal)
 - Possibility to connect a redundant level measurement for alarming purposes (optional for BIOSAFE® narrow neck lines)
 - Mechanical and electrical lid locking (optional for BIOSAFE® narrow neck lines)
 - Temperature monitoring with up to three temperature sensors
 - Other optional equipment: Warmgas bypass, UPS backup battery
- Other clear BIOSAFE® smart plus points are:

 - Audit trail on control actions and settings
 - Networking via TCP/IP or Modbus (option) of up to 256 devices via their own physical, static subnet and a remote desktop connection.
 - Extension to comprehensive cryobank management via BIOSAFE® smart BSIO Box (option)
- Linking options with existing systems via several digital and potential-free inputs and outputs, as well as analog connections
 - PLC function with five freely programmable channels for extensive adaptation to individual Adaptation to individual customer requirements thanks to BIOSAFE® View Software

All from one Source



BIOSAFE® VENUS

With the BIOSAFE® smart for the Venus series, an automatic refill system can be connected conveniently, easily and safely. For the nitrogen supply, the APOLLO® series is available.



Further information concerning APOLLO® series from page 40.

BIOSAFE® VENUS

Order Form.



Item Numbers



Our BIOSAFE® VENUS vessels are available in capacities from 150 to nearly 180 litres.

For your BIOSAFE® VENUS we supply various equipment options and extensive options.

BIOSAFE® VENUS Vessel Options

☒ Item No.	Quantity
☐ 78224110 BIOSAFE® VENUS 150 SC, incl. roller base and connecting hose 1.5 m to APOLLO®, for up to 6 racks, max 8 levels ¹⁾	
☐ 78224404 BIOSAFE® VENUS 150 MD, incl. roller base and connecting hose 1.5 m to APOLLO®, for up to 6 racks, max 8 levels ¹⁾	
☐ 78217554 BIOSAFE® VENUS 150 smart rack for vials 2ml ²⁾ , 8 levels (single item number)	
☐ 78217556 BIOSAFE® VENUS 150 smart rack for goblets with drawers ³⁾ for 4 goblets per level, 3 levels (single item number)	
☐ 78217558 BIOSAFE® VENUS 150 smart rack for 9 cassettes per level, 1 level (single item number)	
☐ 78224111 BIOSAFE® VENUS 180 SC, incl. roller base and connecting hose 1.5 m to APOLLO® for up to 6 racks, max 10 levels ¹⁾	
☐ 78224407 BIOSAFE® VENUS 180 MD, incl. roller base and connecting hose 1.5 m to APOLLO® for up to 6 racks, max 10 levels ¹⁾	
☐ 78217555 BIOSAFE® VENUS 180 smart rack for vials 2ml ²⁾ , 10 levels (single item number)	
☐ 78217557 BIOSAFE® VENUS 180 smart rack for goblets with drawers ³⁾ for 4 goblets per level, 4 levels (single item number)	
☐ 78217559 BIOSAFE® VENUS 180 smart rack for 9 cassettes per level, 2 levels (single item number)	

Factory setting of the BIOSAFE® VENUS-series to gas phase storage, please add item number 78225101 for setting to liquid phase storage.
 1) APOLLO® and racks not included. 2) without cryoboxes 3) without goblets

BIOSAFE® VENUS Extensive Options

☒ Item No.	Quantity
☐ 78217560 Roller base for BIOSAFE® VENUS 150/180 (re-order reference)	
☐ 78212859 Cryobox (10x10, for 100 vials) with Cryotherm label, (single item number)	
☐ 78214364 Cryobox (9x9, for 81 vials) with Cryotherm label, (single article number)	
☐ 78212792 Transparent goblet, without lid, Ø 65 m (single article number)	
☐ 78216990 Set of 5 transparent daisy goblets with 11 coloured inserts, lid, Ø 65 mm (set item number)	
☐ 77031488 Cassette for bags (single article number)	

▶ Our extensive security equipment can be found on pages 6 and 7.

sales@cryotherm.de +49 (0)2741 - 95 85 0

BIOSAFE® MARATHON

For the safe Shipment of your Samples.



Datalogger
for temperature
recordings



All Advantages at a Glance



The safe aluminum dry shipping container for your biological-medical samples.

- ▶ For up to 500 samples, 2 ml vials
- ▶ For up to 6 bags 500 ml
- ▶ Liquid nitrogen can not go out
- ▶ Low temperatures up to -190 C°

Medical
Product
According to
Class IIa

BIOSAFE® MARATHON		25 MD
Dry-Shipper		
Total volume	[l]	25.0
Number of racks	[piece]	1
Dimension of the hybrid racks (HxWxD)	[mm]	297x133x142
2 ml vials	[up to]	500
bags size 280x120x150 mm	[up to]	8


Other dry shipper sizes and accessories on request.

Hybrid rack for bags / vials for
BIOSAFE® MARATHON 25 MD
Item No. 78223756



Bags require protective cassettes.
Capacity deviations are possible
depending on the manufacturer.

Suitable Options for BIOSAFE® MARATHON 25 MD



Roller base for MARATHON 25 with five swivel castors, three of them lockable
Item No. 78224116



2 Robust, lightweight protective packaging MARATHON 25 MD
Item No. 78225807

Height: 861 mm
Outer diameter: 595mm



Protective cap
Item No. 78217562

Extensive safety equipment from page 6



4 Plug with convection barrier
Item No. 78223718

3 and 4 included in the initial scope of delivery

exemplary illustration

BIOSAFE® MARATHON

Order Form.



Technical Data



BIOSAFE® MARATHON

25 MD

Dry-Shipper

Amount of nitrogen absorbed	[l]	9.5
Neck diameter	[mm]	210
Height of sample space	[mm]	305
Total height, without data logger	[mm]	760
Weight, empty, without racks	[kg]	21.5
Weight, full, without racks	[kg]	29
Diameter, outer	[mm]	394
Static holding time ≤ -150°C	[days]*	10

*) The daily evaporation rate and the static holding time were determined at 20 degrees Celsius, 1013 hectopascal, with the vessel standing still, lid closed and without accessories. These are nominal values that may change depending on the use and age of the container.

The BIOSAFE® MARATHON 25 is lockable and sealable*.



*) not included in the scope of delivery

Item numbers



We supply various equipment variants and a wide range of accessories for your BIOSAFE® MARATHON



BIOSAFE® MARATHON

Item No.	Quantity
☐ 78223636 BIOSAFE® MARATHON 25 MD DRYSHIPPER	
☐ 78223756 Hybrid-Rack for BIOSAFE® MARATHON 25 MD DRYSHIPPER	
☐ 78224306 Bluetooth® pdf data logger incl. external PT100 probe	

Other container sizes on request.

BIOSAFE® MARATHON 25 Extensive options / spare parts

Item No.	Quantity
☐ 78224116 Roller base 1	
☐ 78225807 Robust, lightweight protective packaging 2	
☐ 78217562 Protective cap 3 (spare parts)	
☐ 78223718 Plug with convection barrier 4 (spare parts)	

▶ Our extensive security equipment can be found on pages 6 and 7.



sales@cryotherm.de



+49 (0)2741 - 95 85 0



ALPHA

Unpressurised Vessel Series for Small Amounts of Nitrogen.



All Advantages at a Glance





Safe and lightweight storage and transport vessel made in aluminium for liquid nitrogen.

SMALL, COMPACT AND STURDY.

- ▶ Available in three sizes with a capacity of approx. 6, 10 & 25 litres
- ▶ Comprehensive accessories

Withdrawal device for ALPHA 25
For the practical removal of small quantities of liquid nitrogen.
Item No. 78224996



Roller base for ALPHA 25
with five swivel castors, three of them lockable
Item No. 78224116

Technical Data



Storage Capacity ALPHA		5	10	25
Net capacity	[l]	6	10	25
Daily evaporation	[l/Day]*	0.12	0.12	0.12
Static holding time	[Days]*	50	83	208
Weight, empty	[kg]	5	6.2	10.5
Weight, full (filled with LIN)	[kg]	9.7	13.9	31.6
Total height	[mm]	468	528	700
Neck tube diameter	[mm]	50	50	50
Inner diameter	[mm]	231	231	296
Outer diameter	[mm]	300	300	396

*) The daily evaporation rate and the static holding time were determined at 20 degrees Celsius, 1013 hectopascal, with the vessel standing still, lid closed and without accessories. These are nominal values that may change depending on the use and age of the container.

Item Numbers



We supply various equipment variants and a wide range of accessories for your ALPHA.

ALPHA Lines

☒ Item No.		Quantity
☐ 78224172	ALPHA 5, pressureless transport/storage vessel for liquid nitrogen	
☐ 78224173	ALPHA 10, pressureless transport/storage vessel for liquid nitrogen	
☐ 78224174	ALPHA 25, pressureless transport/storage vessel for liquid nitrogen	
☐ 78224116	Roller base for ALPHA 25, with five swivel castors, three of them lockable	
☐ 78224996	Set withdrawal device for ALPHA 25 - including filling hose 1m, cryo protective gloves and safety goggles with side protection	

Other container sizes on request.

JUNO®

Supply Vessel for Cryogenic Liquid Nitrogen

Cryotherm®
life science



All Advantages at a Glance



Supply vessel made in stainless steel for cryogenic liquid nitrogen

SIMPLE, ROBUST, EFFICIENT.

- ▶ Efficient exhaust gas cooling system, optimized super-insulation, compact dimensions, Pressure gauge
- ▶ Integrated safety device on vessel neck
- ▶ Combined positive pressure-relief and seal-off device

Technical Data



Storage Capacity JUNO®		30
Geometrical capacity	[l]	30
Operating overpressure	[bar]	1.3
Empty weight	[kg]	18
Full weight	[kg]	41
Decanting head connection		KF 50
Total height	[mm]	660
Immersion depth	[mm]	533
Outside diameter	[mm]	369
Total width	[mm]	407
Static evaporation rate	[l/day]	0.75



Item Numbers



We supply a wide range of accessories for your Juno® 30.

JUNO® 30

☒ Item No.		Quantity
☐ 78220205	JUNO® 30, 1.3 bar with transport plug	
☐ 78220349	Roller base	
☐ 78220412	Decanting head with waste gas and overflow valve	
☐ 79229957	Decanting hose (1.5 m)	
☐ 79404217	Phase separator	

Special options on request

STELLA®-Series

Liquid Nitrogen „to go“ – your solution for transporting and moving your samples, as well as open working with liquid nitrogen. From a capacity of 0.6 l up to your individualised needs.



STELLA®-Series

For Mobile Nitrogen Use and Open Working



All Advantages at a Glance



- ▶ Design in different sizes and variants
- ▶ STELLA® – for open work in the laboratory
- ▶ STELLA® D – with cover for work in research and industry
- ▶ Special designs, e. g. with gas-tight welded-on stainless steel flange for connection to keeping-cold systems, e. g. detectors

THE STELLA®-LINE

- ▶ Flat bottom | Stable and edge-protected | Also available with blind flange

The STELLA®-Series – the robust vacuum super-insulated dewars for liquid nitrogen use.

Technical Data / Item Number



		STELLA®				STELLA D®		
		65/180	85/205	100/285	185/270	250/450	300/750	400/500
Geometrical capacity	[l]	0.6	1.16	2.23	7.25	22.1	53	62.8
Outside height	[mm]	203	231	312	300	570	870	620
Inside height	[mm]	180	206	285	270	450	750	500
Outside diameter	[mm]	87	107	122	200	305	355	455
Inside diameter	[mm]	65	85	100	185	250	300	400
Lid thickness	[mm]	-	-	-	-	55	55	55
Empty weight	[kg]	0.52	0.86	1.23	2.12	12.5	25.3	30.0
Full weight	[kg]	0.92	1.66	2.83	6.92	27.0	65.3	72.2
Operating overpressure, max	[bar]	0	0	0	0	0	0	0
Item number		0791308	0791309	79408223	0791311	0791081	0791085	0791087
Lid		○	○	○	○	●	●	●
Handle, firm		-	-	-	-	●	●	●
Roller base (Item no. 79233073)		-	-	-	-	-	○	○

● series ○ optional - not available



We look forward to manufacturing dewars in line with your individual design and the exact dimensions you require. Please feel free to contact us for any diameter and / or height.

All Advantages at a Glance



Best in it's class!

Evaporation rate for e.g.
APOLLO® 200: Only 0.6% per day!

A ball valve for comfortable
view: "Open or close"

Ideal operating height and
user-friendly fittings
(ball valves)

Safety Measures at Eye Level

High Stability
for secure and
smooth transport

Time savings through
increased uptime
for your application

Robust Protective Frame
for safe transport

Higher service life with the
following advantages:
Savings in transport and
handling costs

High Quality Design
made of corrosion-resistant
stainless steel

Low Maintenance

Large, stable and
smooth-running wheels
(Ø 125-160 mm) without
sharp edges

Great Mobility
through compact design

Long-term vacuum protection through
high-quality adsorption and getter materials

Including Options



Gloves



exemplary
illustration

Item No.: 0794111

Safety glasses with side protection



Item No.: 0794189

Transfer hose 1,5 m



Item No.: 79229957

(everything included)

Phase separator G 3/8" complete



Item No.: 79404217

Applications

APOLLO®




compatible

- ▶ Analysers
- ▶ Cryogenic mills
- ▶ Cryogenic saunas
- ▶ Freezers
- ▶ Biobanks
- ▶ BIOSAFE®
- ...

Essential Construction Elements and Equipment



- | | |
|---------------------------------------|---|
| 1 Extraction valve | 12 Vacuum sealing and safety valve |
| 2 Exhaust and overflow valve | 13 Superinsulation |
| 3 Pressure build-up valve | 14 Absorbents (long-term vacuum protection) and special getters |
| 4 Pressure gauges | 15 Exhaust and overflow line |
| 5 Safety valve | 16 Sampling line |
| 6 Analog level indicator (opt.) | 17 Pressure build-up line |
| 7 Filling hose | 18 Chassis and protective frame |
| 8 Phase separator | 19 Indoor and outdoor vessel |
| 9 Castors | 20 Gaseous nitrogen |
| 10 Pressure regulator (opt.) | 21 Liquid nitrogen |
| 11 Pressure build-up regulator (opt.) | |



incl. in delivery / standard
digital level indicator

Standard Equipment

- With digital level indicator (APOLLO® 100 - 350) Integrated
- safety device on the vessel neck
- Vacuum seal and safety device
- Smooth-running castors and transport protection frame
- Level and pressure gauge
- EK lift with exhaust and overflow valve
- Integrated pressure build-up
- Filling hose (1.5 m) with phase separator
- Cold protection gloves **1** and safety glasses **2** with side protection



exemplary illustration



for a fixed connection of an APOLLO® urgently required!

Technical Data




Vessel made of Stainless Steel		APOLLO® 50 1.3 bar	APOLLO® 100 1.3 bar	APOLLO® 150 1.3 bar	APOLLO® 200 2.0 bar	APOLLO® 350 2.0 bar
Approval mark		CE	CE	CE	CE0035	CE0035
Geometrical capacity	[l]	49.4	98.8	149.15	199.5	348.7
Operating overpressure max.	[bar]	1.3	1.3	1.3	2.0	2.0
Weight, empty	[kg]	44	62	79	100	160
Weight, full LIN	[kg]	85	145	204	266	450
Stat. evaporation rate LIN	[%/Day]	2	1.2	1	0,6	0.5
Total height incl. digital level ind.	A [mm]	905	1,240	1,580	1,350	1,785
Total height until siphon	B [mm]	765	1,100	1,440	1,170	1,650
Diameter, outer	C [mm]	500	500	500	700	700
Total width	D [mm]	650	650	650	800	800
Depth of immersion	E [mm]	585	920	1,220	910	1,350
Castor diameter	F [mm]	125	125	125	160	160
Neck diameter	G [mm]	50	50	50	50	50
Siphon connection		KF 50	KF 50	KF 50	KF 50	KF 50

Upon request the APOLLO® series is also available for other types of gas.



Our APOLLO®-Series is available with a capacity of 50 to 350 litres

For dimensions see table.



Options

- Pressure build-up regulator (Item No. 78202710)
- Pressure reduction regulator (Item No. 78203080)
- Double extraction liquid side (Item No. 79415416)
- Double extraction gas side (Item No. 78203081)
- Triple extraction liquid side (Item No. 79418082)
- Triple extraction gas side (Item No. 78203082)
- Safety spacer **3** (Item No. 78205899)
- Level indicator, capacitive, battery
- Forklift pockets **6**
- Set of castors, antimagnetic
- Reversion APOLLO® 50/100/150 to 4 bar

Further options available upon request.

- ▶ Our APOLLO® series complies with the European Pressure Equipment Directive 2014/68 / EU

- ▶ Reversion APOLLO® 50/100/150 to 4 bar, incl. pressure reduction regulator Item No. 78224071 (exemplary illustration)



5



The **digital display** – the capacitive level indicator for your APOLLO®

- ▶ Display and probe in one device
- ▶ Easy to use
- ▶ High precision

6



Practical **forklift pockets** facilitate the handling of your APOLLO®

Item Numbers



APOLLO® Liquid Nitrogen Vessel	also available as 4 bar version				
	50	100	150	200	350
with digital level indicator 5	78223343*	78223344	78223345	78223346	78223347
with digital level indicator 4bar 5	78223343/4bar*	78223344/4bar	78223345/4bar		
Options for APOLLO® line					
Forklift pockets 6	78203083	78203083	78203083	78203975	78203900
Set of castors, antimagnetic	78200474	78200474	78200474	78203992	78203992

*) With analog level indicator. Item No. 78202700 or 78202700/4bar



Standard with digital display APOLLO® 100-350



MORE THAN
60
YEARS
Since 1964
**Excellence
in Engineering**

Cryotherm GmbH & Co. KG

Euteneuen 4
D-57548 Kirchen/Sieg, Germany
Telephone: +49 27 41 / 95 85-0
Fax: +49 27 41 / 69 00
E-mail: sales@cryotherm.de



Cryotherm Inc.

5126 South Royal Atlanta Drive
Tucker, GA 30084, USA
Telephone: +1 770-274-2410
Fax: +1 770-934-3384
E-mail: info@cryotherminc.com



Your local contact:



Illustrations may differ. Subject to technical changes.
Version 2066